

REGUPOL CLIMB FX



Material composition:

PUR binders, synthetic rubber components

Areas of application:

Outdoor climbing

Thickness:

50 mm, 75 mm and 110 mm

Weight:

50 mm = approx. 35 kg/m²

75 mm = approx. 46 kg/m²

110 mm = approx. 62 kg/m²

HIC:

Fall protection test according to the playground test DIN EN 1177 (HIC).

50 mm = approx. 1.50 m (max. height of fall)

75 mm = approx. 2.10 m (max. height of fall)

110 mm = approx. 3.00 m (max. height of fall)

Fire classification:

Efl

Cfl -s1 available as a custom-made product

Slip resistance:

R 10

Advantages:

Quick and easy to lay.

Colours:

approx. 21 colours


Mixtures of colours are possible.

Service:


Product sample service, individual worldwide consulting, external certification, internal quality certificates, lines and lettering.

REGUPOL CLIMB FX

EPDM granulate




Red




Bright red




Bright orange




Pink



Lilac




Bright blue




Blue



Dark blue



Bright green



Green



Dark green



Eggshell



Yellow



Bright yellow



Beige



Beige brown



Brown



White



Grey



Middle grey



Dark grey


EPDM mulch



Brown Beige



Green



Red