DECLARATION OF PERFORMANCE



According to appendix III of the Construction Products Regulation (EU) No. 305/2011

DOP NR.: REGUPOL 016

REGUPOL everroll ultimate

Premanufactured elastic flooring product made from EPDM-granules for indoor use unsealed, thicknesses: 4 mm - 12 mm

REGUPOL Germany GmbH & Co.KG | Am Hilgenacker 24 | 57319 Bad Berleburg | Germany

Evaluation of the constancy of performance:	System 3
The notified body	eco Institut Germany GmbH Notified Body No. 2097,
and	MPA NRW Notified Body No. 0432,
based on the European Technical Assessment	ETA-21/0943
of 19 July 2022, in accordance with Regulation (EC) no 305/2010 on basic of:	EAD 190026-00-0502

The initial tests of the product according to System 3 were carried out. A factory production control was established in accordance with the provisions of ETA-21/0943

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	Class C _{fl} -S1	EN 13501-1:2018	
Hygiene, health and the environment (BWR 3)	N-Nitrosamines ≤ 11μg/kg	DIK-Prüfvorschrift	
	Karzinogen (Kat. 1A/1B) 3 days/ 28 days <0,01/<0,001mg/m³	EN 16516:2018-01	
	TVOC _{spez} . 3 days/ 28 days < 10 / 1,0 mg/m³	EN 16516:2018-01	
	TSVOC 28 days		

DECLARATION OF PERFORMANCE



According to appendix III of the Construction Products Regulation (EU) No. 305/2011

	< 0,1 mg/m³		
	TVOC ohne NIK 28 days < 0,1 mg/m³ R-Wert < 1 (28 days)	EN 16516:2018-01	
PAK-content	Performance not relevant	(does not contain recycled rubber)	
Tensile at break (6mm thickness)	≥ 1300 kPa	Test according to DIN EN ISO 1798	
Elongation at break (6mm thickness)	≥ 100%	Test according to DIN EN ISO 1798	
Gliding performance	Class DS	Test according to EN 13893	
Electrostatic behaviour	antistatic (≤2,0 kV)	Test according to EN 1815	
Compressive stress (6mm thickness)	≥ 4500 kPa Test according to DIN EN ISO 3386- 2 bei 25% deformation		
Thermal conductivity	$\lambda = 0.36 \text{ W/(mK)}$ Test according to EN 12664:2001		

The performance of the **Regupol everroll ultimate** product and the corresponding batches are in accordance with the above figures. This declaration of performance is issued under the sole responsibility of the manufacturer **REGUPOL Germany GmbH & Co.KG**.

Signed for the manufacturer and on behalf of the manufactures by:

C -	L 	D : 1	1000
se	pastian	Pöppel	/ CEO

(Name and Role)

Bad Berleburg, 01.08.2022

(Place/Date of issue)

(Signature)