

DECLARATION OF PERFORMANCE

According to appendix III of the Construction Products Regulation (EU)
No. 305/2011



DOP NR.: REGUPOL 019

REGUPOL everroll vitality

Premanufactured elastic flooring product made from EPDM and SBR rubber granules for indoor use
EN 14041:2008, unsealed, thicknesses: 4 mm - 12 mm

REGUPOL Germany GmbH & Co.KG | Am Hilgenacker 24 | 57319 Bad Berleburg | Germany

Evaluation of the constancy of performance:

System 3

The notified body

**eco Institut Germany GmbH Notified
Body No. 2097,**

has made the determination of the product on the basis of a system 3 type

Essential characteristics	Performance	Harmonised technical specification
Class of fire behavior according to EN 13501-1	Klasse E _{fl}	EN 14041 : 2008
Content of Pentachlorophenol	DL (<0,5ppm)	EN 14041 : 2008
Formaldehyd Emission EN 717-2	E1 (<0,124mg/m ³)	EN 14041 : 2008
Slip-resistant according to EN 13893	DS (≥0,3)	EN 14041 : 2008
Electrical behavior EN 1815	antistatic (<2,0kV)	EN 14041 : 2008
Thermal conductivity EN 12667	approximately 0,11W/(mK)	EN 14041 : 2008
Water tightness EN 13553	NPD	EN 14041 : 2008

The performance of the **everroll vitality** product and the corresponding batches are in accordance with the above figures. This declaration of performance is issued under the sole responsibility of the manufacturer **REGUPOL Germany GmbH & Co.KG**.

Signed for the manufacturer and on behalf of the manufactures by:

Sebastian Pöppel / CEO

(Name and Role)

Bad Berleburg, 02.10.2023

(Place/Date of issue)

(Signature)

