

TENDER TEXT

REGUPOL PLAYFIX GAME



Playing field surfacing according to DIN V 18035-6

Proof of delivery

REGUPOL GmbH & Co. KG

Am Hilgenacker 24
57319 Bad Berleburg
+49 2751 803-0
info@regupol.de
www.regupol.com

Proof of suitability

test

acc. to

DIN V18035-6

By testing institute:
Test certificate from:
Test certificate no.:

Position	Quantity	Scope of services	Unit price	Total
1	linear metres	Protect surrounding edgings, drainage channels and adjacent components with adhesive tape and foil against contamination by synthetic mass, including removal and proper disposal after the synthetic has been installed.	linear meter/€	€
2	m ²	REGUPOL playfix game – Synthetic floor in accordance with DIN V 18035-6, water-permeable, deliver and install professionally. Floor type: B according to DIN V 18035-6 Description: Loose-coated surface Base layer: Polyurethane bound rubber granulate, poured. Layer thickness: Approx. 25 mm Top layer: Polyurethane bound EPDM granulate, poured. Layer thickness: Approx. 10 mm Surface: EPDM granulate, stored flat Colour: Red Total thickness: Approx. 35 mm	m ² /€	€
3		Marking lines and points for the following playing fields: ... according to the guidelines of the respective sport associations with UV-resistant 2-component PUR paint, matched to the installed synthetic floor.	flat rate	€

Total: €