PRODUCT INFORMATION



REGUPOL EVERROLL ALPINE EL



Product:

tile product made of PUR-bonded EPDM-granulates, with 100 % EPDM colour content

Application Areas:

mountain and base stations, hospitality (outdoor areas)

Features:

durable, sustainable, de-icing salt resistant, weatherproof, non-slip, quickly laid, trafficable

Thickness:

30 mm

Standard Dimension:

 $1,000 \times 500$ mm, dummy joint at 500 mm

Weight:

approx. 23.0 kg/m²

Slip Resistance:

R 10 based on DIN 51130 (02.2014) and ASR A1.5/1,2

Impact Resistance:

> 21 Nm based on EN 14904 / EN 1517

Force Reduction:

up to 59% based on EN 14904 / EN 14808



Certificate of sustainability:

Cradle to Cradle Certified® is a registered trademark of the Cradle to Cradle Products Innovation Institute.

REGUPOL everroll alpine EL is Cradle to Cradle Certified $^{\circ}$ at the Bronze level.

Fire Classificatin:

 $C_{\rm fl}$ -s1 based on EN 13501-1:2018

Salt Water Resistance:

resistant based on DIN EN ISO 175

Colours

two colours, individual colours available on request

Further technical data is available on request.



PRODUCT INFORMATION



REGUPOL EVERROLL ALPINE EL

REGUPOL everroll alpine EL





Dekor 1 [5105|5106*]

Dekor 2 [5107|5104*]

* = increased light fastness only when used indoors

Deviations from the colours shown are possible due to production batches and brochure print.

We reserve the right to make changes to the technical data. The test results and specified values are subject to a tolerance of +/-10 %. Crucial for the up-to-date data is the information on our homepage www.regupol.com.